

## **PRODUCT NO.** 5399-25

## DOTLUX LED glass tube NANOTUBE 97cm 12W 4000K frosted






- Excellent durability due to UV-resistant, non-yellowing glass.
- Glass cover allows better light effect
- Simple replacement of fluorescent tubes with starter
- The full, optimum light output immediately after switching on

ONLY AVAILABLE AS A PACKAGE UNIT (25 pieces)!

State.

to the product page



SUCCESSION ARTICLE	-	BEAM ANGLE	220°
PREDECESSOR ARTICLE	2747-240180	PROTECTION CLASS (IP)	IP20
		TEMPERATURE RANGE	-20°C to +45°C
WEIGHT IN KG	0.145	LIGHT COLOR	neutral white
LUMEN PER WATT	160	INPUT VOLTAGE	220-240 V AC
POWER CONSUMPTION IN WATTS	12	COLOR TEMPERATURE IN KELVIN	4000
NET LUMINOUS FLUX IN LUMENS	1920	FREQUENCY RANGE IN HZ	50/60
CONSUMPTION (KWH/1000H)	12	COLOR-RENDERING-INDEX	CRI > 82
		BASE	G13
		BEG FUNDING	Only relevant in Germany
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	С
Dimensions		COVER MATERIAL	Glass satined
		LIFETIME L80/B10 AT 25°C	30000
length: 982mm		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
diameter: 28mm		POWER FACTOR	> 0,9